

VSH XPress

VSH XPress Copper Gas ensures that safety is paramount by offering swift, flame-free installation alongside assuring consistent high-quality and performance for your commercial gas system.



SG1 Straight Coupler

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	




SG1S Slip Coupler

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	



SG1FMF PN16 Flange

67mm x 2.1/2"
76mm x 3"
108mm x 4"



SG2 Female BSP Adaptor

15mm x 1/2"	35mm x 1.1/4"
22mm x 3/4"	42mm x 1.1/2"
28mm x 1"	54mm x 2"



SG3 Male BSP Adaptor

15mm x 1/2"	54mm x 2"
22mm x 3/4"	67mm x 2.1/2"
28mm x 1"	76mm x 3"
35mm x 1.1/4"	108mm x 4"
42mm x 1.1/2"	



SG6 Insert Reducer

22x15mm	42x22mm
28x15mm	42x28mm
28x22mm	42x35mm
35x22mm	54x28mm
35x28mm	54x35mm



SG6 Insert Reducer

54x42mm	76x54mm
67x28mm	76x67mm
67x35mm	108x42mm
67x54mm	108x54mm
76x35mm	108x67mm




SG6 Insert Reducer

54x42mm	76x54mm
67x28mm	76x67mm
67x35mm	108x42mm
67x54mm	108x54mm
76x35mm	108x67mm
76x42mm	108x76mm



SG11 Union

15mm	35mm
22mm	42mm
28mm	54mm



SG12 90° Elbow

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	



SG12S 90° Street Elbow

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	



SG21 45° Elbow

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	



SG21S 45° Street Elbow

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	




SG24 Equal Tee

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	



SG27 End & Branch Red Tee

22x15x15mm



SG30 BSP Branch Tee

15x15x1/2"
22x22x1/2"
22x22x3/4"
28x28x1/2"
28x28x3/4"
35x35x1/2"
42x42x1/2"
54x54x1/2"
76x76x1/2"
108x108x1/2"
89x89x3/4"
108x108x3/4"



SG61 End Cap

15mm	54mm
22mm	67mm
28mm	76mm
35mm	108mm
42mm	




Copper Gas

- BSI Kitemark approved (BS 8537:2010) from 12mm to 108mm
- Temperature rating from -20 C to 70 C
- Max working pressure inside = 1 bar, outside = 5 bar
- Safer installation due to no naked flames or heat required
- Wide range of British and International Approvals
- No Leak Before Press feature for safety reasons
- HNBR yellow o ring and prominent marking on exterior of fitting ensure clear identification of system