

Copper Pressfittings 12mm – 108mm (Stock range shown)
 WRAS/KIWA Approved. Suitable for Hot/Cold & Heating Services

<p>SAN1 6270</p> <p>Straight Coupling</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 	<p>SAN6 6243</p> <p>Reducer Insert</p> <p>22x15mm 42x22mm 28x15mm 28x22mm 35x22mm 35x28mm</p> 	<p>SAN12s 6001A</p> <p>90 Street Elbow</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 
<p>SAN2 8270G</p> <p>Female Adaptor</p> <p>15mmx½ 22mmx¾ 28mmx1 35mmx1¼ 42mmx1½</p> 	<p>SAN6 6243</p> <p>Reducer Insert</p> <p>42x 28mm 42x35mm 54x35mm 54x42mm 67x28mm</p> 	<p>SAN21 6041</p> <p>45 Elbow F/F</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 
<p>SAN2 8270G</p> <p>Female Adaptor</p> <p>54mmx2 67mmx2½ 76mmx2½</p> 	<p>SAN6 6243</p> <p>Reducer Insert</p> <p>67x35mm 67x42mm 67x54mm 76x42mm 76x54mm</p> 	<p>SAN21s 6040</p> <p>45 Str Elbow M/F</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 
<p>SAN3 8243G</p> <p>Male Adaptor</p> <p>15mmx½ 22mmx¾ 28mmx1 35mmx1¼ 42mmx1½</p> 	<p>SAN6 6243</p> <p>Reducer Insert</p> <p>76x67mm 108x42mm 108x54mm 108x67mm 108x76mm</p> 	<p>SAN24 6130</p> <p>Tee Equal</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 
<p>SAN3 8243G</p> <p>Male Adaptor</p> <p>54mmx2 67mmx2½ 76mmx3 108mmx4</p> 	<p>SAN12 6002A</p> <p>90 Elbow</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 	<p>SAN25 6130</p> <p>Tee Red Branch</p> <p>22x15mm 35x28mm 28x15mm 42x15mm 28x22mm 42x22mm 35x15mm 35x22mm</p> 

Sanha Copper Pressfittings upto 54mm can be crimped with any press-on clamps & crimping tools available in the market for metal crimp connections (Regular maintenance is absolutely necessary for all tool/clamps & calibration every 12 months)

Copper fittings to BS EN12449 gunmetal fittings to BS EN1982.

Copper pipe to correspond to EN1057 or BS2871

Max temp 120C max pressure PN16, for indication only see manufacturers temp/pressure graph.

Sanha offer a full range of fittings for gas, solar heating (200C), compressed air, stainless steel material & valves including radiator, ball valves & manifolds.

Additional size fittings available please see Sanha full catalogue.

SYSTEM TECHNOLOGY OF SANHA

More Comfortable - Fairer - Safer

SANHA[®]

www.sanha.com

Copper Pressfittings 12mm – 108mm (Stock range shown)
WRAS/KIWA Approved. Suitable for Hot/Cold & Heating Services

<p>SAN25 6130</p> <p>Tee Red Branch</p> <p>42x28mm 54x42mm 42x35mm 67x28mm 54x22mm 54x28mm 54x35mm</p> 	<p>SAN27 6130</p> <p>Red Tee</p> <p>22x15x15mm 28x22x15mm 28x22x22mm</p> 	<p>SAN69 8333G</p> <p>Male Union</p> <p>15mmx1/2 22mmx3/4 28mmx1</p> 
<p>SAN25 6130</p> <p>Tee Red Branch</p> <p>67x35mm 76x35mm 67x42mm 76x42mm 67x54mm 76x54mm 76x22mm 76x28mm</p> 	<p>SAN30 8130G</p> <p>BSP Branch Tee</p> <p>15mmx1/2 22mmx1/2 22mmx3/4 28mmx1/2</p> 	<p>SAN69 8333G</p> <p>Male Union</p> <p>35mmx1/4 42mmx1/2 54mmx2</p> 
<p>SAN25 6130</p> <p>Tee Red Branch</p> <p>76x67mm 108x54mm 108x67mm 108x76mm</p> 	<p>SAN30 8130G</p> <p>BSP Branch Tee</p> <p>35mmx1/2 42mmx1/2 54mmx1/2</p> 	<p>SAN1F BMPF</p> <p>Flange PN10/16</p> <p>28mm 76mm 35mm 108mm 42mm 54mm 67mm</p> 
<p>SAN26 6130</p> <p>One End Red Tee</p> <p>22x15x22mm 28x22x28mm</p> 	<p>SAN61 6301</p> <p>End Cap</p> <p>15mm 54mm 22mm 67mm 28mm 76mm 35mm 108mm 42mm</p> 	<p>SAN7 8246G</p> <p>F/I BSP Insert</p> <p>15mmx1/2 54mmx2 22mmx3/4 28mmx1 35mmx1/4 42mmx1/2</p> 

SANHA®-Press – - the all rounder



SANHA® System press fittings	Operational temperature
SANHA®-Press system fitting with EPDM gasket	-30 °C – +120 °C
SANHA®-Press Gas system fittings with HNBR gasket	-20 °C – +70 °C
SANHA®-Press Solar system fittings with FKM gasket	-20 °C – +200 °C (depending on the medium)
Type of threading: Connecting thread: R/Rp thread according to EN 10226 Fastening screw thread: G thread according to EN/ISO 228	