

Primofit compression fitting is a time saving pipe jointing system for steel & mdpe pipework. Ease of installation without the need for specialist tools is an important feature allowing connections to plain ended pipe.

<p><b>Coupling</b></p> <p>1/2-3" Stl x Stl Galvanised, NBR Seals</p> <p>20-63mm PE x PE Black, NBR Seals</p>		<p><b>90 Elbow</b></p> <p>1/2-2" Stl x Stl Galvanised, NBR Seals</p> <p>20-63mm PE x PE Black, NBR Seals</p>	
<p><b>Male Adaptor</b></p> <p>1/2-3" Stl x BSP Galvanised, NBR Seals</p> <p>20-63mm PE x BSP, Black, NBR Seals</p>		<p><b>Tee</b></p> <p>1/2-2" Stl x Stl Galvanised, NBR Seals</p> <p>20-63mm PE x PE Black, NBR Seals</p>	
<p><b>Female Adaptor</b></p> <p>1/2-3" Stl x BSP Galvanised, NBR Seals</p> <p>20-63mm PE x BSP Black, NBR Seal</p>		<p><b>Cap</b></p> <p>1/2-2" Stl x Stl Galvanised, NBR Seals</p> <p>20-63mm PE x PE Black, NBR Seals</p>	

FIRE JOINT FITTINGS & POTABLE WATER COUPLINGS ARE AVAILBLE ON REQUEST

MEDIUM	APPLICATION	MAX TEMP	MAX PRESSURE	FINISH	SEAL
Water	Non Potable	80C	16BAR	GALV	NBR
LP Gas	Above Ground	70C	10BAR	GALV	NBR
Natural Gas	Below Ground	70C	10BAR	BLACK	NBR
Oil	Fuel Oil	40C	16BAR	BLACK	NBR
Compressed Air	Supply Lines	105C	10BAR	GALV	FPM
Diesel/Petrol	Fuel Lines	40C	10BAR	BLACK	FPM
Water	Heating Systems	105C	6BAR	BLACK	FPM

The Viking Johnson Maxifit range has been designed to join pipes of various diameters. These fittings can be used on steel, ductile iron, cast iron and pvc-u pipes. The Easi Range, Aquagrip, Flexlock & fabricated couplings are available on request.

SIZE	COUPLING	FLANGE ADAPTOR	O/D RANGE
1 1/2	VJC101	*	48-59MM
2	VJC102	VJC201	57-74MM
2 1/2	VJC103	VJC201A	72-85MM
3	VJC104	VJC202	85-107MM
4	VJC105	VJC203	107-128MM
5	VJC106	VJC204	139-153MM
6	VJC107	VJC205	158-181.6MM
8	VJC108	VJC206	219-234MM
10	VJC110	VJC207	265-280MM
12	VJC115	VJC208	324-338MM

SIZE	MINI REPAIR CLAMP	O/D RANGE
1/2	REPAIR101	21-25MM
3/4	REPAIR102	26-30MM
1	REPAIR103	33-37MM
1 1/4	REPAIR104	42-46MM
1 1/2	REPAIR105	47-51MM
2	REPAIR106	60-64MM

